



## Introduction

The Atлона Gain™ 60 (**AT-GAIN-60**) is a compact power amplifier designed for low or high impedance applications. A mode selector switch allows the Gain 60 to deliver two channels of 30 watts each into 4 or 8 ohms, or a single channel of 60 watts at 24, 70, or 100 volts. This Class-D amplifier is energy-efficient and ENERGY STAR® qualified, and is also convection-cooled without the need for fans. Additionally, the Gain 60 is UL 2043 plenum-rated, allowing convenient yet discreet installation in a plenum airspace above a drop ceiling. Balanced and unbalanced inputs are provided for system design versatility. The Gain 60 is controllable via TCP/IP or RS-232, and can be integrated with Atлона AV switchers and OmniStream™ AV systems for a wide variety of sound reinforcement applications.

## Applications

- Meeting rooms, huddle rooms, and classrooms**  
 The Gain 60 can receive audio from an AV switcher or DSP, and then feed the audio to program speakers on the front wall, or a distribution of ceiling speakers.
- Plenum airspaces**  
 The Gain 60 can easily be concealed above a drop ceiling, minimizing the need for AV equipment space in a room.

### Key Features

- Selectable low or high impedance operation.
- 2 x 30 watts @ 4 or 8 ohms.
- 1 x 60 watts @ 24, 70, or 100 volts.
- Selectable balanced and unbalanced audio inputs.
- Class-D efficient amplifier design.
- ENERGY STAR qualified.
- Convection cooled – no need for fans.
- UL 2043 plenum-rated – allows installation above commercial drop ceilings.
- Automatic standby, configurable from 5 to 25 minutes of inactivity, to minimize power consumption.
- Rear panel input level control.
- Integrated protection circuitry automatically activates in the event of clipping, short circuit, thermal overload, and more.
- Bass and treble tone controls.
- TCP/IP and RS-232 control of volume level, muting, and tone controls.
- Ideal for IP-based control from Atlona Velocity™ Control System.
- Front-panel button controls for input selection, mute, and volume control.
- Front-panel signal status LEDs for power, input selection, mute, and volume level.
- Compact, rack-mountable enclosure.
- Optional AT-RACK-1RU rack shelf – recommended for rack installation.
- Includes installation guide, captive screw connectors, and external universal power supply.

### Specifications

Input Signal	
Analog	Balanced: 20 k $\Omega$ , unbalanced: 10 k $\Omega$
Gain	Adjustable, -22 dB to 0 dB
CMRR	49 dB / 67 dB
Wake Up Threshold	0 dBV = 2.218 dBu, available on Rev B and above

Output Signal	
Distributed speakers (mono)	24 V / 70 V / 100 V
Program speakers (stereo)	4 $\Omega$ / 8 $\Omega$ , line-level
Power	24 V = 60 W 70 V = 60 W 100 V = 60 W 4 / 8 $\Omega$ = 30 W per channel

Audio Processing	
Audio Formats	24-bit uncompressed, selectable at 44.1, 48, 88.2, and 96 kHz sampling rate
Signal Processing	Volume, Auto on/off signal sensing, 80Hz HPF
2-band EQ	Bass / Treble, adjustable: -10 to +10 dB

Audio Performance	
Frequency Response	20Hz - 20kHz, $\pm 0.2$ / - 2 dB @ 4 $\Omega$ load
THD + N	< 0.1% @ 1kHz, 3 dB below clipping
SNR	> 95 dBA WTD
Damping Factor	< 48 @ 8 $\Omega$
Amplifier Type	Class D

Temperature	Fahrenheit	Celsius
Operating	32 °F to 122 °F	0 °C to 50 °C
Storage	-40 °F to 158 °F	-40 °C to 70 °C
Humidity (RH)	90% RH, non-condensing	

Power	
Standby Mode	Powers down after 5 - 25 minutes (adjustable) of no signal; complies with ENERGY STAR power consumption limits of < 0.5W in standby mode
Consumption	60W (max.)
Standby Consumption	< 1.2W
Supply	100 - 240 VAC, 50/60Hz, 60W

Connectors, Controls, and Indicators	
LAN	1 - RJ45
AUDIO IN 1	1 - 5-pin captive screw, balanced: 10 k $\Omega$
AUDIO IN 2	2 - RCA-type, female, unbalanced: 20 k $\Omega$
4 / 8 $\Omega$ OUT	1 - 4-pin, 5.08 mm lock-down screw connector
24 / 70 / 100V	1 - 2-pin, 5.08 mm lock-down screw connector
Power	1 - Barrel, locking
INPUT GAIN	1 - Rotary pot
MODE	1 - Slider switch, 5-pole, 24V / 70V / 100V / 8 $\Omega$ / 4 $\Omega$
Control Buttons: INPUT, MUTE, VOL, RESET	4 - Push button, tact-type
Reset Button	
Input Indicators: 1, 2	2 - LED indicators, green
Mute Indicator	1 - LED indicator, red
Audio Level Indicator	1 - Multi-LED

Dimensions (H x W x D)	Inches	Millimeters
Unit	1.69 x 5.00 x 7.95	43 x 127 x 202

Weight	Pounds	Kilograms
Device	3.15	1.43

Certification	
Device	CE, FCC, CB, RoHS, WEEE, FCC, ENERGY STAR®

### Copyright, Trademark, and Registration

© 2023 Atlona Inc. All rights reserved. "Atlona" and the Atlona logo are registered trademarks of Atlona Inc. Pricing, specifications and availability subject to change without notice. Actual products, product images, and online product images may vary from images shown here.

All other trademark(s), copyright(s), and registered technologies mentioned in this document are the properties of their respective owner(s).