

## Release Notes

### Public Releases

Version 1.2.03	
Features	<ul style="list-style-type: none"> <li>Redesigned web server UI for end-user configuration.</li> <li>Resources product control templates available for download on AT-ANC-108D product page.</li> </ul>
Bug Fixes	<ul style="list-style-type: none"> <li>Addressed several UI issues within the AT-ANC-108D web server.</li> <li>Several security improvements have been implemented (session-aware web server).</li> <li>Improved the reliability of loading configuration files.</li> </ul>
Known Issues	<ul style="list-style-type: none"> <li>None</li> </ul>

### Previous Releases

Version 1.1.15	
Features	<ul style="list-style-type: none"> <li>None</li> </ul>
Bug Fixes	<ul style="list-style-type: none"> <li>Fixed an issue where polling would cause the toggle function to be disabled.</li> <li>Fixed an issue where hex values 00 and 0D would be switched when placed at the front and end of command strings, respectively.</li> <li>Corrected a spelling error that was displayed when an incorrect username or password was entered.</li> <li>Fixed an issue where setting the IP timeout period could not exceed 1000 minutes.</li> </ul>
Known Issues	<ul style="list-style-type: none"> <li>None</li> </ul>

Version 1.1.09	
Features	<ul style="list-style-type: none"> <li>Added toggle state tracking, which monitors the power state of the device that has been powered. For example, if the AT-ANC-108D is used to power-on the AT-UHD-SW-510W, and the AT-UHD-SW-510W is powered off at the unit, the AT-ANC-108D will recognize the new power state, allowing the toggle button to, once again, power-on the AT-UHD-SW-510W.               <ul style="list-style-type: none"> <li>» MacroToggle. MacroToggle sta X X=1-16 Macro ID. MacroToggle X Y X=1-16 Macro ID., Y=0-1(0: macro 1-8, 1: macro 9-16)</li> </ul> </li> <li>Added the ability to manage the hostname using the SHostName and RHostName commands.</li> <li>Added the device hostname as part of a query, when executing the "System sta" command.</li> </ul>
Bug Fixes	<ul style="list-style-type: none"> <li>Improved accuracy in timing for repeated commands.</li> <li>Resolved rendering issues within the webUI in Google Chrome version 73.0.3683.103.</li> <li>Improved accuracy in timing for polling intervals.</li> <li>Resolved an issue where if a button was set to toggle mode, pressing the button would execute both the ON and OFF macros from a single button press.</li> <li>Implemented a function that will ignore button pressing, while an ON or OFF macro is running on a single button. This would result in executing both the ON and OFF macros at the same time.</li> <li>Resolved an issue where performing a factory reset would cause the unit to assign a static IP address.</li> </ul>
Known Issues	<ul style="list-style-type: none"> <li>None</li> </ul>

## Release Notes

### Version 1.1.01

Features	<ul style="list-style-type: none"><li>Improved functionality of the “Broadcast off” feature, which optimizes syncing with AMS.</li></ul>
Bug Fixes	<ul style="list-style-type: none"><li>Fixed lock-up issue.</li><li>Decreased the reboot time from every 24 hours to every 8 hours.</li></ul>
Known Issues	<ul style="list-style-type: none"><li>None</li></ul>

### Version 1

- Factory Firmware