



IP DRIVER FOR ATLONA AT-JUNO-451 FOUR-INPUT SWITCHER

This driver allows you to control an Atlona AT-JUNO-451 Four-Input Switcher from Control4.

INSTALLATION INSTRUCTIONS

- Ensure the Atlona Switcher is at the most recent firmware level.
- Set the Atlona Switcher to a static IP address or ensure it always receives the same IP address from the DHCP server via a MAC-based reservation.
- Connect the Inputs and Outputs as appropriate.
- **Recommended:** disable AutoSwitch via the Web UI (A/V Settings, Video: set Auto Switch to OFF).
- Refresh Navigators.

USAGE NOTES

- When 'Power Off when Unused' is set to Yes, the driver will power the Switcher Off when its room is Off. When powering back On, the driver will insert a 20-second delay before sending a switching command.
- Programming commands are available to manage the Toslink output, as well as the audio on the HDMI output.

SUPPORT

For support on this driver please go to <http://www.atlona.com/product-support/>. If required, give a detailed description of the problem and also include the version number of the driver and the version of Control4 OS that you are using.

CHANGELOG

1.0.0 December 31, 2019 Initial BETA Release

Developed by Domosapiens Inc. for Atlona Inc.
Copyright 2019, Domosapiens Inc.
All Rights Reserved