

## Update Instructions

**IMPORTANT NOTE:** A factory reset must be performed after this update. Additionally, if you are currently on Beta firmware 1.3.29 you will be required to update the firmware via USB method. Refer to the next page for instructions.

The switcher can be updated through webGUI and USB.

Needed items (webGUI):

- New firmware - Downloaded from either atlona.com or through a box.com link sent by a Technical Support representative
- IP address of the Switcher
- Computer on the same network as the Switcher
- Username and password to access the webGUI of the Switcher

Needed items (USB):


- New firmware - Downloaded from either atlona.com or through a box.com link sent by a Technical Support representative
- Mini USB to USB A cable
- Computer with a USB port
- Switcher and included power supply

### Updating (webGUI)

1. Plug a LAN cable into the switcher and your network router (if not already connected to the network)
2. Type the IP address of the switcher into a web browser (as seen below).



**NOTE:** Computer must be on the same network as the switcher to access through IP



**IMPORTANT:** If any stability issues are experienced, disable any anti-virus or firewall that may be interfering with network communication to the switcher. Once set up is done and the webGUI is no longer being used, the firewall and anti-virus can be re-enabled.



Login

Username

Password

Submit


A login screen will appear (this is the same log in for admin and general users).

3. Login using the username and password (this would have been set up during installation)

## Update Instructions

Once logged in:

4. Select the link named 'Network'



5. Select the browse button under Firmware Update
6. Select the new firmware file that was downloaded either from atlona.com or box.com
7. Press the update button

A progress bar will display as the update is completed. After the update is complete, if a restart is required, the webGUI will display a prompt. The firmware update is now complete and the switcher is ready to be used.


## Updating (USB)

Putting the unit into update mode:


1. Unplug the power from the HD-SC-500
2. Press and hold the display key
3. Plug the power back into the HD-SC-500 (while still holding the display key)
4. Continue holding the display key for 5 seconds then release it
5. Connect HD-SC-500 to a computer using the mini USB to USB A cable

Updating:

6. Click the option, "Open folder to view files" (if AutoPlay runs)



## Update Instructions



**NOTE:** If the computer does not auto detect the connection, open “My Computer” and select the USB drive.

7. Place the latest firmware in the folder (if there is already a file in the folder, delete it)
8. Remove the USB cable from the HD-SC-500 and computer
9. Unplug the power cable from the HD-SC-500
10. Plug the power cable back in

The update process is complete and the switcher is ready to be used